Asymptote Reference Card

Program structure/functions

`import "`*filename*`"`	import module
`import "`*filename*`" as name`	import filename as module name
`include "`*filename*`"`	include verbatim text from file
type f`(`*type*`,...);`	optional function declaration
type name`;`	variable declaration
type f`(`*type arg*`,...) {`	function definition
statements	
`return` *value*`;`	
`}`	

Data types/declarations

boolean (true or false)	`bool`
tri-state boolean (true, default, or false)	`bool3`
integer	`int`
float (double precision)	`real`
ordered pair (complex number)	`pair`
character string	`string`
fixed piecewise cubic Bezier spline	`path`
unresolved piecewise cubic Bezier spline	`guide`
color, line type/width/cap, font, fill rule	`pen`
label with position, alignment, pen attributes	`Label`
drawing canvas	`picture`
affine transform	`transform`
constant (unchanging) value	`const`
allocate in higher scope	`static`
no value	`void`
inhibit implicit argument casting	`explicit`
structure	`struct`
create name by data type	`typedef` *type name*

3D data types (import three;)

ordered triple	`triple`
3D path	`path3`
3D guide	`guide3`
3D affine transform	`transform3`

Constants

exponential form	`6.02e23`
TEX string constant	`"abc...de"`
TEX strings: special characters	`\\, \"`
C strings: constant	`'abc...de'`
C strings: special characters	`\\, \" \' \?`
C strings: newline, cr, tab, backspace	`\n \r \t \b`
C strings: octal, hexadecimal bytes	`\0-\377 \x0-\xFF`

Operators

arithmetic operations	`+ - * /`
modulus (remainder)	`%`
comparisons	`== != > >= < <=`
not	`!`
and or (conditional evaluation of RHS)	`&& ||`
and or xor	`& | ^`
cast expression to type	`(`*type*`)` *expr*
increment decrement prefix operators	`++ --`
assignment operators	`+= -= *= /= %=`
conditional expression	$expr_1$ `?` $expr_2$ `:` $expr_3$
structure member operator	*name*`.`*member*
expression evaluation separator	`,`

Flow control

statement terminator	`;`
block delimeters	`{ }`
comment delimeters	`/* */`
comment to end of line delimiter	`//`
exit from `while`/`do`/`for`	`break;`
next iteration of `while`/`do`/`for`	`continue;`
return value from function	`return` *expr*`;`
terminate execution	`exit();`
abort execution with error message	`abort(string);`

Flow constructions (`if`/`while`/`for`/`do`)

`if(`*expr*`)` *statement*
`else if(`*expr*`)` *statement*
`else` *statement*

`while(`*expr*`)`
statement

`for(`$expr_1$`;` $expr_2$`;` $expr_3$`)`
statement

`for(`*type* `var :` *array*`)`
statement

`do` *statement*
`while(`*expr*`);`

Arrays

array	*type*`[] `*name*`;`
array element i	*name*`[i]`
array indexed by elements of int array `A`	*name*`[A]`
anonymous array	`new `*type*`[`*dim*`]`
array containing `n` deep copies of `x`	`array(n,x)`
length	*name*`.length`
cyclic flag	*name*`.cyclic`
pop element `x`	*name*`.pop()`
push element `x`	*name*`.push(x)`
append array `a`	*name*`.append(a)`
insert rest arguments at index `i`	*name*`.insert(i,...)`
delete element at index `i`	*name*`.delete(i)`
delete elements with indices in [`i`,`j`]	*name*`.delete(i,j)`
delete all elements	*name*`.delete()`
test whether element n is initialized	*name*`.initialized(n)`
array of indices of initialized elements	*name*`.keys`
complement of int array in `{0,...,n-1}`	`complement(a,n)`
deep copy of array `a`	`copy(a)`
array `{0,1,...,n-1}`	`sequence(n)`
array `{n,n+1,...,m}`	`sequence(n,m)`
array `{n-1,n-2,...,0}`	`reverse(n)`
array `{f(0),f(1),...,f(n-1)}`	`sequence(f,n)`
array obtained by applying `f` to array `a`	`map(f,a)`
uniform partition of [`a`,`b`] into n intervals	`uniform(a,b,n)`
concat specified 1D arrays	`concat(a,b,...)`
return sorted array	`sort(a)`
return array sorted using ordering `less`	`sort(a,less)`
search sorted array `a` for key	`search(a,key)`
index of first true value of bool array `a`	`find(a)`
index of nth true value of bool array `a`	`find(a,n)`

Initialization

initialize variable	*type name*`=`*value*`;`
initialize array	*type*`[] `*name*`={...};`

path connectors

straight segment	`--`
Beziér segment with implicit control points	`..`
Beziér segment with explicit control points	`..controls c0 and c1..`
concatenate	`&`
lift pen	`^^`
..tension atleast 1..	`::`
..tension atleast infinity..	`---`

Labels

implicit cast of string `s` to Label	`s`
Label `s` with relative position and alignment	`Label(s,real,pair)`
Label `s` with absolute position and alignment	`Label(s,pair,pair)`
Label `s` with specified pen	`Label(s,pen)`

draw commands

draw path with current pen	`draw(path)`
draw path with pen	`draw(path,pen)`
draw labeled path	`draw(Label,path)`
draw arrow with pen	`draw(path,pen,Arrow)`
draw path on picture	`draw(picture,path)`
draw visible portion of line through two pairs	`drawline(pair,pair)`

fill commands

fill path with current pen	`fill(path)`
fill path with pen	`fill(path,pen)`
fill path on picture	`fill(picture,path)`

label commands

label a pair with optional alignment z	`label(Label,pair,z)`
label a path with optional alignment z	`label(Label,path,z)`
add label to picture	`label(picture,Label)`

clip commands

clip to path	`clip(path)`
clip to path with fill rule	`clip(path,pen)`
clip picture to path	`clip(picture,path)`

pens

Grayscale pen from value in [0,1]	`gray(g)`
RGB pen from values in [0,1]	`rgb(r,g,b)`
CMYK pen from values in [0,1]	`cmyk(r,g,b)`
RGB pen from heximdecimal string]	`rgb(string)`
heximdecimal string from rgb pen]	`hex(pen)`
hsv pen from values in [0,1]	`hsv(h,s,v)`
invisible pen	`invisible`
default pen	`defaultpen`
current pen	`currentpen`
solid pen	`solid`
dotted pen	`dotted`
wide dotted current pen	`Dotted`
wide dotted pen	`Dotted(pen)`
dashed pen	`dashed`
long dashed pen	`longdashed`
dash dotted pen	`dashdotted`
long dash dotted pen	`longdashdotted`
PostScript butt line cap	`squarecap`
PostScript round line cap	`roundcap`
PostScript projecting square line cap	`extendcap`
miter join	`miterjoin`
round join	`roundjoin`
bevel join	`beveljoin`
pen with miter limit	`miterlimit(real)`
zero-winding fill rule	`zerowinding`
even-odd fill rule	`evenodd`
align to character bounding box (default)	`nobasealign`
align to TEX baseline	`basealign`
pen with font size (pt)	`fontsize(real)`
LaTeX pen from encoding,family,series,shape	`font(strings)`
TEX pen	`font(string)`
scaled TEX pen	`font(string,real)`
PostScript font from strings	`Courier(series,shape)`
pen with opacity in [0,1]	`opacity(real)`
construct pen nib from polygonal path	`makepen(path)`
pen mixing operator	`+`

path operations

number of segments in path `p`	`length(p)`
number of nodes in path `p`	`size(p)`
is path `p` cyclic?	`cyclic(p)`
is segment `i` of path `p` straight?	`straight(p,i)`
is path `p` straight?	`piecewisestraight(p)`
coordinates of path `p` at time `t`	`point(p,t)`
direction of path `p` at time `t`	`dir(p,t)`
direction of path `p` at `length(p)`	`dir(p)`
unit(dir(p)+dir(q))	`dir(p,q)`
acceleration of path `p` at time `t`	`accel(p,t)`
radius of curvature of path `p` at time `t`	`radius(p,t)`
precontrol point of path `p` at time `t`	`precontrol(p,t)`
postcontrol point of path `p` at time `t`	`postcontrol(p,t)`
arclength of path `p`	`arclength(p)`
time at which `arclength(p)=L`	`arctime(p,L)`
point on path `p` at arclength `L`	`arcpoint(p,L)`
first value `t` at which `dir(p,t)=z`	`dirtime(p,z)`
time `t` at relative fraction `l` of `arclength(p)`	`reltime(p,l)`
point at relative fraction `l` of `arclength(p)`	`relpoint(p,l)`
point midway along arclength of `p`	`midpoint(p)`
path running backwards along `p`	`reverse(p)`
subpath of `p` between times `a` and `b`	`subpath(p,a,b)`
times for one intersection of paths `p` and `q`	`intersect(p,q)`
times at which `p` reaches minimal extents	`mintimes(p)`
times at which `p` reaches maximal extents	`maxtimes(p)`
intersection times of paths `p` and `q`	`intersections(p,q)`
intersection times of path `p` with '`--a--b--`'	`intersections(p,a,b)`
intersection times of path `p` crossing $x =$`x`	`times(p,x)`
intersection times of path `p` crossing $y =$`z.y`	`times(p,z)`
intersection point of paths `p` and `q`	`intersectionpoint(p,q)`
intersection points of `p` and `q`	`intersectionpoints(p,q)`
intersection of extension of `P--Q` and `p--q`	`extension(P,Q,p,q)`
lower left point of bounding box of path `p`	`min(p)`
upper right point of bounding box of path `p`	`max(p)`
subpaths of `p` split by `n`th cut of `knife`	`cut(p,knife,n)`
winding number of path `p` about pair `z`	`windingnumber(p,z)`
pair `z` lies within path `p`?	`interior(p,z)`
pair `z` lies within or on path `p`?	`inside(p,z)`
path surrounding region bounded by paths	`buildcycle(...)`
path filled by `draw(g,p)`	`strokepath(g,p)`
unit square with lower-left vertex at origin	`unitsquare`
unit circle centered at origin	`unitcircle`
circle of radius `r` about `c`	`circle(c,r)`
arc of radius `r` about `c` from angle `a` to `b`	`arc(c,r,a,b)`
unit `n`-sided polygon	`polygon(n)`
unit `n`-point cyclic cross	`cross(n)`

pictures

add picture `pic` to currentpicture	`add(pic)`
add picture `pic` about pair `z`	`add(pic,z)`

affine transforms

identity transform	`identity()`
shift by values	`shift(real,real)`
shift by pair	`shift(pair)`
scale by `x` in the x direction	`xscale(x)`
scale by `y` in the y direction	`yscale(y)`
scale by `x` in both directions	`scale(x)`
scale by real values `x` and `y`	`scale(x,y)`
map $(x, y) \to (x+$`s`$y, y)$	`slant(s)`
rotate by real `angle` in degrees about pair `z`	`rotate(angle,z=(0,0))`
reflect about line from `P--Q`	`reflect(P,Q)`

string operations

concatenate operator	`+`
string length	`length(string)`
position $\geq$ `pos` of first occurence of `t` in `s`	`find(s,t,pos=0)`
position $\leq$ `pos` of last occurence of `t` in `s`	`rfind(s,t,pos=-1)`
string with `t` inserted in `s` at `pos`	`insert(s,pos,t)`
string `s` with `n` characters at `pos` erased	`erase(s,pos,n)`
substring of string `s` of length `n` at `pos`	`substr(s,pos,n)`
string `s` reversed	`reverse(s)`
string `s` with `before` changed to `after`	`replace(s,before,after)`
string `s` translated via `{{before,after},...}`	`replace(s,string [][] table)`
format `x` using C-style format string `s`	`format(s,x)`
casts hexadecimal string to an integer	`hex(s)`
casts `x` to string using precision `digits`	`string(x,digits=realDigits)`
current time formatted by `format`	`time(format="%a %b %d %T %Z %Y")`
time in seconds of string `t` using `format`	`seconds(t,format)`
string corresponding to `seconds` using `format`	`time(seconds,format)`
split `s` into strings separated by `delimiter`	`split(s,delimiter="")`

May 2014 v1.1. Copyright © 2014 John C. Bowman

Permission is granted to make and distribute copies of this card, with or without modifications, provided the copyright notice and this permission notice are preserved on all copies.